RM2 MULTIPURPOSE HOSE - EPDM HOSE



RM2 is a good quality and economical multipurpose EPDM hose recommended for water and air, as well as many other industrial and construction uses (not suitable for petroleum products) up to 2" diameters. It is reinforced with textile cord and has excellent weather and abrasion resistance. -40F to 190F.

QT	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
Υ	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	1/4			1/2	200	1 1/2	0.09
	1/4			17/32	250	2 1/2	0.11
	1/4			17/32	300	3. 25	0.1
	5/16			5/8	200	3 1/4	0.12
	3/8			21/32	200	3 1/2	0.17
	3/8			23/32	250	3 1/2	0.17
	3/8			23/32	300	4	0.17
	1/2			13/16	200	4 1/2	0.2
	1/2			7/8	250	4 3/4	0.22
	1/2			7/8	300	4 3/4	0.22
	5/8			1	250	5 1/2	0.27
	3/4			1 5/32	250	5 3/4	0.35
	3/4			1 5/32	300	6 1/4	0.37
	1			1 7/16	200	6 1/2	0.54
	1 1/4			1 3/4	200	8	0.75
	1 1/2			2	200	10	0.86
	2			2 1/2	200	12	1.16

NOTES: THE HOSE IS RATED FOR -40 TO 190 DEG F.

CUSTOMER PROJECT ENGINEER	PROJECT		FLE ICRAFT "Flexible Piping Solutions"		
CONTRACTOR		MODEL:	RM2		
CERTIFICATION		DRAWN BY:	MULTIPURPOSE		
		PDB 8/04	HOSE - EPDM		
HOSECRAFT USA 2315 W. HUBI	PHONE: 800	PHONE: 800-584-4168 FAX: 312-421-6327			