RT1 STEAM HOSE



RT1 is a rubber steam hose with a heat resistant EPDM tube and cover for maximum life. It is used for cleaning, thawing, steam pumps, heat control, and many other all around steam applications.

Usually used with ground joint fittings. Also available in Butyl.

-20F to 415F.

| QT Y | INNER DIA | OAL | FITTINGS | OUTER DIA | PRESSURE | BEND RADIUS | WEIGHT |
|---------|--------------|------|----------|-----------|----------|----------------|----------|
| ' | (in) | (in) | | (in) | (psi) | (in) | (lbs/ft) |
| | 1/2 | | | 1 | 250 | - | 0.4 |
| | 3/4 | | | 1 1/4 | 250 | - | 0.49 |
| | 1 | | | 1 5/8 | 250 | - | 0.78 |
| | 1 1/4 | | | 1 15/16 | 250 | - | 0.83 |
| | 1 1/2 | | | 2 1/8 | 250 | - | 1.03 |
| | 2 | | | 2 3/4 | 250 | 1 | 1.88 |
| | 3 | | | 3 11/16 | 250 | - | 2.73 |

NOTES: THE HOSE IS RATED FROM -20F TO 415F. ALSO AVAILABLE IN ANY OTHER ELASTOMER.

| CUSTOMER | ELE | CICRAFT | |
|---------------|-----------------------------|-------------------|--|
| PROJECT | "Flexible Piping Solutions" | | |
| ENGINEER | FICKIDIC | riping Solutions | |
| CONTRACTOR | MODEL: | RT1 | |
| CERTIFICATION | DRAWN BY: | RUBBER STEAM HOSE | |
| | PDB 1/1/04 | NOBBER OTEAM HOOL | |

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 800-584-4168 FAX: 312-421-6327