

RH2 RUBBER OUTER CONVOLUTED HOSE



RH2 is a versatile and rugged highly abrasive resistant smooth bore rubber transfer hose that can be cut to fit. It is used with our split high grade aluminum (150#) flanges, which bolt together and conform to the outer convolutions for a secure field fit.

-25F to 180F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	2		SPLIT 150# ALUM FLG	3.000	250	12	2
	3		SPLIT 150# ALUM FLG	4.555	250	14	4
	4		SPLIT 150# ALUM FLG	5.432	200	20	6
	5		SPLIT 150# ALUM FLG	6.456	175	26	8
	6		SPLIT 150# ALUM FLG	7.596	150	30	10
	8		SPLIT 150# ALUM FLG	9.898	150	69	13
	10		SPLIT 150# ALUM FLG	11.730	150	79	15
	12		SPLIT 150# ALUM FLG	13.720	150	99	19
	14		SPLIT 150# ALUM FLG	16.198	150	119	26

NOTES: THE HOSE IS RATED FOR -25 F TO 180 F.

*ALSO AVAILABLE IN ANY OTHER ELASTOMER, AND UP TO 24" DIAMETERS.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 "Flexible Piping Solutions"						
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%;">RH2</td> </tr> <tr> <td>DRAWN BY:</td> <td>RUBBER MATERIAL HANDLING HOSE</td> </tr> <tr> <td>PDB 1/1/04</td> <td></td> </tr> </table>	MODEL:	RH2	DRAWN BY:	RUBBER MATERIAL HANDLING HOSE	PDB 1/1/04	
MODEL:	RH2						
DRAWN BY:	RUBBER MATERIAL HANDLING HOSE						
PDB 1/1/04							