

PD1 PVC LAYFLAT HOSE



The Model PD1 is a blue PVC discharge lay-flat hose that resists kinking and twisting. It is designed as a standard duty hose for water discharge in industrial and construction applications, is strong and economical, and rolls up flat for easy storage. Reinforcement includes spiral plies and longitudinal synthetic cords for excellent burst resistance. Other varieties for higher pressures alternate materials are also available.

Can come with aluminum coupling fittings with (M)NPSM threads and aluminum/brass swivels in standard lengths. Commonly provided with cam and groove or threaded coupling fittings and hose nozzles.

Temperature range is -5F to 170F. Pressure drops above 110F.

QTY	INNER DIA	OAL	FITTINGS	PRESSURE	WEIGHT	COIL LENGTHS
	(in)	(ft)		(psi)	(lbs/100ft)	(ft)
	1 1/2			80	19	300
	2			80	25	300
	2 1/2			65	30	300
	3			80	36	300
	4			70	53	300
	6			60	86	300
	8			35	130	300
	10			35	188	100
	12			35	240	100
	14			30	270	100
	16			30	300	100

NOTES: Also available in standard duty blue.

CUSTOMER _____	 "Flexible Piping Solutions"	
PROJECT _____		
ENGINEER _____	MODEL:	PD1
CONTRACTOR _____	DRAWN BY:	PVC DISCHARGE
CERTIFICATION _____	PDB 1/1/04	