
## COMPENSATOR SWEAT ENDS



Flexicraft Compensators are perfect for pipe diameters up to 4" when axial movement is requried due to thermal expansion. They are stocked with both 2" and 3" compression ability in flanged, weld, thread, and sweat ends.



Maximum Working Pressu	ure 150 psi
Working Temperature	20F -500F
Test Pressure	250 psi
Bellows	. Multi-Ply T304 S/S

## NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

Dimensions			Movements		Physicals				
Pipe	Туре	Length	В	Axial	Axial	Effective	Spring	Weight	Product No.
Size	Type	А		Comp	Ext.	Area	Rate		rioudet No.
in	S/L	in	in	in	in	in²	lbs/in	lbs	
0.75	S	11	1.63	2	0.5	1.1	82	0.75	COMPS20075
0.75	L	14.38	1.63	3	0.5	1.1	58	1	COMPS30075
1	S	11.25	2	2	0.5	1.7	89	1	COMPS20100
1	L	15.13	2	3	0.5	1.7	63	1.5	COMPS30100
1.25	S	12.5	2.25	2	0.5	2.4	75	1.5	COMPS20125
1.25	L	16.38	2.25	3	0.5	2.4	54	2	COMPS30125
1.5	S	12.88	2.5	2	0.5	3.2	74	2	COMPS20150
1.5	L	16.75	2.5	3	0.5	3.2	52	3	COMPS30150
2	S	13	3	2	0.5	5.1	168	3	COMPS20200
2	L	17	3	3	0.5	5.1	118	4	COMPS30200
2.5	S	13.25	4	2	0.5	7.6	188	4	COMPS20250
2.5	L	17	4	3	0.5	7.6	110	5	COMPS30250
3	S	14	4.5	2	0.5	10.6	251	4.5	COMPS20300
3	L	18	4.5	3	0.5	10.6	175	6	COMPS30300
4	S	15.06	5.88	2	0.5	17.9	341	9	COMPS20400
4	L	19	5.88	3	0.5	17.9	241	12	COMPS20400
FLE Proposal/Inquiry/Order No.: NOTES:   "Flexible Piping Solutions" Project Name: Project Name:									
PRINT CER		N:	Contra	ctor: sators by Flexicraft co		performance and			

FLEXICRAFT INDUSTRIES 2315 W. HUBBARD ST., CHICAGO, IL 60612

economy. They can usually be provided quickly.